



MATERIAL SAFETY DATA SHEET

Revised: 6/27/00

Product Name: NEPTCO Products (P26FWB)
Chemical: Polypropylene film, aluminum foil with water swellable coating, blue Ethylene Acrylic film laminate

Supplier: NEPTCO Incorporated
30 Hamlet Street
Pawtucket, RI 02861

Product Information: 1-401-722-5500

Emergency Information: 1-800-451-8346

I. HAZARDOUS INGREDIENTS & EXPOSURE LIMITS

<u>Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits</u>
Poly (sodium acrylate) homopolymer	Not Est. cas #9003-04-7	Not Est.	Not Est.
Poly (2-ethyl - 2-oxazoline)	Not Est. cas #25805-17-8	Not Est.	Not Est.
2-ethyl - 2 oxazoline	Not Est. cas #10431-98-8	Not Est.	Not Est.

This product is considered an article under OSHA and TSCA standards.

If this product is used in a manner that could generate particulates (dust), NEPTCO recommends that the dust be treated as a "NUISANCE PARTICULATE" (Particulates Not Otherwise Classified) as defined by the American Conference of Governmental Industrial Hygienists (ACGIH) or (Particulates Not Otherwise Regulated) as defined by OSHA. This material is considered an article under OSHA and TSCA standards.

II. PHYSICAL DATA

Appearance and Odor:	White one side, blue on opposite side
Boiling Point (°F):	N/A
Vapor Pressure (mm Hg):	N/A
Vapor Density (Air = 1):	N/A - Solid material
Solubility in Water:	Coating only
Specific Gravity:	avg. 1.7
Volatile (Wt.) %:	Non-volatile
pH:	N/A
Evaporation Rate:	N/A
Melting Point:	N/A

This material will burn if exposed to flame. Fire fighters should protect themselves from combustion products that may include hydrogen bromide, bromine carbon dioxide, carbon monoxide, and other organic vapors. Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to products of combustion exists. Fire and extinguishing media include water, carbon dioxide, foam or dry chemical.

Chemical Stability:	Stable
Incompatibilities:	None reasonably foreseeable
Decomposition Products:	Via incomplete combustion only (see Section III)
Polymerization:	Will not occur

Conditions to Avoid: Material may be attacked by oxidizing agents, such as nitric or per-chloric acid and free halogens. Also softened by hydrocarbons such as benzene, gasoline, lubricating oils, petroleum ether, and by chlorinated hydrocarbons. Products can decompose at elevated temperatures. Avoid direct sunlight.

V. HEALTH HAZARD DATA

Exposure Limits:	N/A
Toxicity Data:	N/A
Cancer Information:	Contains no NTP or OSHA listed carcinogens.
Primary Rte of Exposure:	Skin contact and inhalation.
Effects of Overexposure:	It is unlikely that any potential health hazards will be expressed.
Emergency First Aid Procedures:	It is not anticipated that any first-aid requirements will be necessary from normal industrial handling of this material.

VI. APPLICABLE CONTROL MEASURES

Appropriate Hygienic Practices:	Wash hands thoroughly after handling, and before eating, drinking, or smoking.
Personal Protective Equipment:	Not normally required.

VII. ENVIRONMENTAL DATA

Spill and Leak Procedure:	Broken pieces, cuttings, or other debris should be swept or vacuumed.
Waste Disposal:	Used or unused product should be disposed of in accordance with Federal, State, or Local laws or regulations.

Disclaimer:

The information presented in this MSDS was obtained from sources which NEPTCO believes are reliable; however, the information is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness.

NEPTCO Incorporated
Department of Regulatory Affairs
Box 2323, 30 Hamlet Street
Pawtucket, RI 02861-0323 USA
Web site: www.neptco.com
E-mail: dlloyd@neptco.com
TEL: 401 722-5500 FAX: 401 725-9962