



MATERIAL SAFETY DATA SHEET

Issued: 4/5/10

1. PRODUCT AND COMPANY INFORMATION

Product Names: WBY and NPY Series Polyester Waterblocking Yarns

Chemical Name: Polymer-based matrix on polyester, which may also be coated with a hydrophilic polymer.

Company Information:
NEPTCO JV LLC
30 Hamlet Street
Pawtucket, RI 02861
(401) 722-5500

Product Information: 401-722-5500

Emergency Information: 800-451-8346

2. HAZARDOUS INGREDIENTS & EXPOSURE LIMITS

None as defined under OSHA Hazard Communication Standard 29 CFR 1910.1200 or under SARA Title III, Section 313. This material is considered an article under OSHA and TSCA standards.

If this product is used in a manner that could generate particulates (dust), NEPTCO recommends that the dust be treated as a "NUISANCE PARTICULATE" (Particulates Not Otherwise Classified) as defined by the American Conference of Governmental Industrial Hygienists (ACGIH) or (Particulates Not Otherwise Regulated) as defined by OSHA.

3. HAZARD IDENTIFICATION

Exposure Limits: Not applicable

Cancer Information: Contains no NTP or OSHA listed carcinogens.

Primary Route of Exposure: Skin contact.

Effects of Overexposure: Temporary skin, eye, and upper respiratory mucous membrane irritation.

4. FIRST AID MEASURES

Skin: Wash thoroughly with soap and water.

Eyes: Flush with running water for 15 minutes.

Mucous Membranes: Seek fresh air or consult a physician. If irritation persists, consult a physician.

5. FIRE AND EXPLOSION HAZARD DATA

This material will burn if exposed to flame. Fire fighters should protect themselves from combustion products that may include hydrogen chloride, carbon dioxide, carbon monoxide and other toxic gases. Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to products of combustion exists. Fire and extinguishing media include water, carbon dioxide, foam or dry chemical.

NEPTCO Product WBYP and NPY Series Polyester Waterblocking Yarns**6. ACCIDENTAL RELEASE MEASURES**

Spill and Leak Procedures: Broken pieces, cuttings, or other debris should be swept or vacuumed.

7. STORAGE

Store in cool, dry, and ventilated area. Protect against physical damage. Store away from ignition sources.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Appropriate Hygienic Practices: Wash thoroughly after handling, and before eating, drinking or smoking.
Personal Protective Equipment: Safety glasses, cloth gloves, protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor:	Milky white or yellowish with no odor.
Boiling Point (°F):	N/A
Vapor Pressure (mm Hg):	N/A
Vapor Density (Air = 1):	N/A – Solid Material
Solubility in Water:	Negligible
Specific Gravity:	N/A
Volatile (Wt.) %:	<1
pH:	N/A
Evaporation Rate:	N/A
Melting Point:	250°C

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable
Incompatibilities:	None reasonably foreseeable
Decomposition Products:	Via incomplete combustion only (see Section III)
Polymerization:	Will not occur
Conditions to Avoid:	None expected.

11. TOXICOLOGICAL INFORMATION

Not available at this time

12. ECOLOGICAL INFORMATION

Not available at this time

13. DISPOSAL CONSIDERATIONS

Used or unused product should be disposed of in accordance with Federal, State, or Local laws or Regulations.

14. TRANSPORT INFORMATION

USDOT: Not Regulated

NEPTCO Product WBY and NPY Series Polyester Waterblocking Yarns

15. REGULATORY INFORMATION

Regulatory References:

- OSHA: Occupational Health and Safety Administration
- NTP: National Toxicology Program
- USDOT: United States Department of Transportation
- TSCA: Toxic Substances Control Act (USA)
- SARA: Superfund Amendments and Reauthorization Act

16. OTHER INFORMATION

The information presented in this MSDS was obtained from sources which NEPTCO believes are reliable; however, the information is provided without any representation or warranty, expressed or implied, regarding accuracy or correctness.

NEPTCO Incorporated
Box 2323, 30 Hamlet Street
Pawtucket, RI 02861-0323
Web site: www.neptco.com
E-mail: efranklin@neptco.com
TEL: 401-722-5500 FAX: 401-725-9962